

(43) International Publication Date  
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number  
WO 2005/061116 A1

(51) International Patent Classification<sup>7</sup>: B05B 1/24

(21) International Application Number: PCT/KR2004/003395

(22) International Filing Date: 22 December 2004 (22.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 10-2003-0096983  
24 December 2003 (24.12.2003) KR

(71) Applicant (for all designated States except US): RESEARCH INSTITUTE OF INDUSTRIAL SCIENCE & TECHNOLOGY [KR/KR]; San 32, Hyoja-dong, Nam-ku, Pohang, Kyungsangbook-do, 790-330 (KR).

(72) Inventors; and  
(75) Inventors/Applicants (for US only): KIM, Hyung-Jun


(74) Agent: C & S PATENT AND LAW OFFICE; C-2306 Daelim Acotel, 467-6 Dogok-dong, Kangnam-gu, Seoul 135-971 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: COLD SPRAY APPARATUS HAVING POWDER PREHEATING DEVICE



(57) Abstract: There is provided a cold spray apparatus having a powder preheating device, capable of obtaining high deposition rate and excellent coating layer under the same spray processing conditions by preheating coating powder before a coating process. Also, there is provided a manufacturing method of nano-structured super-high hardness WC-Co coating having high abrasive wear resistance and fracture toughness by spraying WC-Co powder using the cold spray apparatus. In the cold spray apparatus, a gas controller controls gas supply amount of main gas and residual gas (gas that is not supplied toward the main gas), and a gas heater heats the main gas supplied under the control of the gas controller. A powder feeder receives the residual gas under the control of the gas controller and supplies a coating powder together with the residual gas. A powder preheating device preheat the coating powder supplied from the powder feeder, and a mixing chamber mixes the heated main gas with the preheated coating powder. A temperature controller adjusts temperature by controlling the powder preheating device and the gas heater, and the coating powder mixed in the mixing chamber is sprayed through a nozzle.

WO 2005/061116 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*